

Double-Sided Window Display Datasheet

Category	Parameter	Front Screen (Semi-Outdoor Window Side)	Rear Screen (Indoor Side)
Panel	Screen Size	55"	
	Panel Technology	ADS	
	Backlight Technology	Direct	
	Aspect Ratio	16:9	
	Native Resolution	1920 × 1080	
	Refresh Rate	60 Hz	
	Brightness	2000 nits	1000 nits
	Contrast Ratio	1000:1	
	Color Gamut	72% NTSC	
	Viewing Angle	178° × 178° (H/V)	
	Response Time	14 ms (GtG)	
	Surface Treatment	Anti-Glare / Matte Finish (AGLR)	
	Operating Hours	7 × 16	
Connectivity	Input	HDMI, USB × 2, MIC IN	
	Output	Audio Output; External Speaker (L/R, 6 W + 6 W)	
Mechanical	Bezel Color	Black	
	Bezel Width	8.8 mm (uniform on L/R/Bottom sides)	
	Dimensions (W×H×D)	703 × 1277.7 × 96.8 mm (W×H×D)	
	Net Weight	45 kg	
Features	Key Features	Dual-Screen Independent Display Support	
Environment	Operating Temperature (No Direct Sunlight)	0 °C – 40 °C	
	Operating Temperature (Direct Sunlight)	0 °C – 30 °C (cooling system recommended for direct sunlight)	
	Operating Humidity	10% – 80% RH	
Power	Power Input	AC 100 – 240 V ~, 50/60 Hz	
	Power Supply Type	Built-in PSU (Internal)	
Power Consumption	Typical	≤380 W	
	Off Mode	≤0.5 W	
Language	OSD Language	Multi-language (Chinese, English, etc.)	
Accessories	Standard Accessories	Remote Control, Power Cord, HDMI Cable, User Manual (EIG, IG), IR Receiver (Ambient Light Sensor)	