

Outdoor Floor Standing Display – Type A Datasheet

Category	Parameter	43"	55"	65"	75"	86"
Panel	Screen Size	43"	55"	65"	75"	86"
	Panel Technology	ADS	IPS	IPS	IPS	IPS
	Backlight Technology	Direct	Direct	Direct	Direct	Direct
	Aspect Ratio	16:9	16:9	16:9	16:9	16:9
	Native Resolution	1920 × 1080	3840 × 2160	3840 × 2160	3840 × 2160	3840 × 2160
	Refresh Rate	60 Hz	60 Hz	60 Hz	60 Hz	60 Hz
	Brightness	3500 nits (Peak 4000 nits)	3500 nits (Peak 4000 nits)	3500 nits (Peak 4000 nits)	3500 nits (Peak 4000 nits)	3500 nits (Peak 4000 nits)
	Contrast Ratio	1200:1	1200:1	1200:1	1200:1	1200:1
	Color Gamut	72% NTSC	73% NTSC	68% NTSC	69% NTSC	72% NTSC
	Viewing Angle	178° × 178° (H/V)	178° × 178° (H/V)	178° × 178° (H/V)	178° × 178° (H/V)	178° × 178° (H/V)
	Response Time	8 ms (GtG)	8 ms (GtG)	8 ms (GtG)	8 ms (GtG)	8 ms (GtG)
	Protection Glass	AR/AG Anti-Glare & Anti-Reflective Coating (Transmittance ≥95%)				
	Operating Hours	24/7	24/7	24/7	24/7	24/7
Connectivity	Input	HDMI, USB × 2				
Mechanical	Cabinet Color	Black (Custom RAL colors available upon request)				
	Dimensions (W×H×D)	729 × 1832 × 160 mm	880 × 2100 × 160 mm	1003 × 2320 × 160 mm	1127 × 2500 × 220 mm	1265 × 2745 × 220 mm
	Net Weight	130 kg	160 kg	200 kg	260 kg	320 kg
Key Features	System & Customization	Support In-depth System Customization				
Environment	IP Rating	IP65				
	Operating Temperature	-30 °C – 50 °C				
	Operating Humidity	10% – 80% RH				
Power	Power Input	AC 100 – 240 V ~, 50/60 Hz				
	Power Supply Type	Built-in PSU (Internal)				
Power Consumption	Typical	≤250 W	≤350 W	≤430 W	≤500 W	≤600 W
	Off Mode	≤0.5 W	≤0.5 W	≤0.5 W	≤0.5 W	≤0.5 W
Audio	Built-in Speakers	5 W × 2				
Language	OSD Language	Multi-language (Chinese, English, etc.)				
Accessories	Standard Accessories	Remote Control, Power Cord, HDMI Cable, User Manual, IR Receiver, Ambient Light Sensor				